

# Morsetti da quadro

## Terminal blocks



Articolo GRIGIO Item GREY		<b>CTS2</b>	<b>CTS4</b>	<b>CTS6</b>	<b>CTS10</b>								
Articolo BLU Item BLUE		<b>CTS2N</b>	<b>CTS4N</b>	<b>CTS6N</b>	<b>CTS10N</b>								
Certificazioni Approval													
Altezza x lunghezza x spessore Height x length x thickness		46.2 x 43 x 5 mm	46.2 x 43.0 x 6 mm	47.8 x 43.0 x 8 mm	47.8 x 43.0 x 10 mm								
Conduttori connettabili Connection Possibility	Flessibili Flexible	0.25 ÷ 2.5 mm <sup>2</sup>	0.25 ÷ 4.0 mm <sup>2</sup>	0.5 ÷ 6.0 mm <sup>2</sup>	0.5 ÷ 10.0 mm <sup>2</sup>								
	Rigidi Solid	0.25 ÷ 4.0 mm <sup>2</sup>	0.25 ÷ 6.0 mm <sup>2</sup>	0.5 ÷ 10.0 mm <sup>2</sup>	0.5 ÷ 16.0 mm <sup>2</sup>								
Lunghezza spelatura cavo Cable stripping length		9 mm	9 mm	9 mm	12 mm								
		IEC 60947-7-1	UL 1059	CSA 22.2-158	IEC 60947-7-1	UL 1059	CSA 22.2-158	IEC 60947-7-1	UL 1059	CSA 22.2-158	IEC 60947-7-1	UL 1059	CSA 22.2-158
Tensione nominale Voltage Rating		1000 V	600 V	600 V	1000 V	600 V	600 V	1000 V	600 V	600 V	1000 V	600 V	600 V
Corrente nominale Current Rating		24 A	20 A	25 A	32 A	40 A	40 A	41 A	50 A	50 A	57 A	65 A	65 A
Coppia di serraggio Tightening torque range		0.4 Nm	7 lb-in	7 lb-in	0.5 Nm	7 lb-in	7 lb-in	0.8 Nm	14 lb-in	14 lb-in	1.2 Nm	14 lb-in	14 lb-in

Terminale - End plate		<b>CE2.4</b>	<b>CE2.4</b>	<b>CE6.10</b>	<b>CE6.10</b>
Diaframma - Partition plate		<b>CP2.4</b>	<b>CP2.4</b>	<b>CP6.10</b>	<b>CP6.10</b>
Blocchetto terminale End clamp		<b>CA702</b>	<b>CA702</b>	<b>CA702</b>	<b>CA702</b>
		<b>CA802</b>	<b>CA802</b>	<b>CA802</b>	<b>CA802</b>
Ponte di parallelo preassemblato  Preassembled shorting links		2 poli - poles <b>CA721.2</b> I <sub>max</sub> 24 A	2 poli - poles <b>CA722.2</b> I <sub>max</sub> 32 A	2 poli - poles <b>CA723.2</b> I <sub>max</sub> 41 A	2 poli - poles <b>CA724.2</b> I <sub>max</sub> 57 A
		3 poli - poles <b>CA721.3</b> I <sub>max</sub> 24 A	3 poli - poles <b>CA722.3</b> I <sub>max</sub> 32 A	3 poli - poles <b>CA723.3</b> I <sub>max</sub> 41 A	3 poli - poles <b>CA724.3</b> I <sub>max</sub> 57 A
		4 poli - poles <b>CA721.4</b> I <sub>max</sub> 24 A	4 poli - poles <b>CA722.4</b> I <sub>max</sub> 32 A	4 poli - poles <b>CA723.4</b> I <sub>max</sub> 41 A	4 poli - poles <b>CA724.4</b> I <sub>max</sub> 57 A
		10 poli - poles <b>CA721.10</b> I <sub>max</sub> 24 A	10 poli - poles <b>CA722.10</b> I <sub>max</sub> 32 A	10 poli - poles <b>CA723.10</b> I <sub>max</sub> 41 A	10 poli - poles <b>CA724.10</b> I <sub>max</sub> 57 A



CTS16			CTS25			CTS35			CTS70			CTS120		
CTS16N			CTS25N			CTS35N			CTS70N			CTS120N		
47.8 x 43.0 x 12 mm			57.2 x 49 x 12 mm			59.2 x 50.5 x 16 mm			71.1 x 77.3 x 20.5 mm			83.0 x 84.5 x 27 mm		
0.25 ÷ 16 mm <sup>2</sup>			4.0 ÷ 25.0 mm <sup>2</sup>			4.0 ÷ 35.0 mm <sup>2</sup>			10.0 ÷ 70.0 mm <sup>2</sup>			25.0 ÷ 120.0 mm <sup>2</sup>		
0.25 ÷ 16 mm <sup>2</sup>			4.0 ÷ 25.0 mm <sup>2</sup>			4.0 ÷ 35.0 mm <sup>2</sup>			10.0 ÷ 70.0 mm <sup>2</sup>			25.0 ÷ 120.0 mm <sup>2</sup>		
16 mm			18 mm			18 mm			22 mm			24 mm		
IEC 60947-7-1	UL 1059	CSA 22.2-158	IEC 60947-7-1	UL 1059		IEC 60947-7-1	UL 1059	CSA 22.2-158	IEC 60947-7-1	UL 1059		IEC 60947-7-1	UL 1059	
1000 V	600 V	600 V	1000 V	600 V		1100 V	600 V	600 V	1600 V	1000 V		2000 V	1000 V	
76 A	85 A	70 A	101 A	85 A		125 A	130 A	130 A	192 A	160 A		269 A	240 A	
1.2 Nm	14 lb-in	14 lb-in	2.0 Nm	18 lb-in		2.5 Nm	25 lb-in	25 lb-in	3.0 Nm	35 lb-in		6.0 Nm	90 lb-in	

		CP25		CP35					
CA702		CA702		CA702		CA202		CA202	
CA802		CA802		CA802					
2 poli - poles	<b>CA751.2</b> I <sub>max</sub> 76 A	2 poli - poles	<b>CA725.2</b> I <sub>max</sub> 101 A	2 poli - poles	<b>CA771.2</b> I <sub>max</sub> 125 A				
3 poli - poles	<b>CA751.3</b> I <sub>max</sub> 76 A	3 poli - poles	<b>CA725.3</b> I <sub>max</sub> 101 A	3 poli - poles	<b>CA771.3</b> I <sub>max</sub> 125 A				
4 poli - poles	<b>CA751.4</b> I <sub>max</sub> 76 A	4 poli - poles	<b>CA725.4</b> I <sub>max</sub> 101 A	4 poli - poles	<b>CA771.4</b> I <sub>max</sub> 125 A				
10 poli - poles	<b>CA751.10</b> I <sub>max</sub> 76 A	10 poli - poles	<b>CA725.10</b> I <sub>max</sub> 101 A	10 poli - poles	<b>CA771.10</b> I <sub>max</sub> 125 A				

# Morsetti da quadro

## Terminal blocks




Portafusibile  
Fuse Terminal



Portafusibile  
Fuse Terminal



Doppio livello  
Double level



Triplo livello  
Triple level

Articolo Item	CF4			CF4-060V (6V/60V)			CF4-220V (110V/220V)			CDL4			CTL2.5U		
Certificazioni Approval	UL <sub>us</sub> CE			UL <sub>us</sub> CE			UL <sub>us</sub> CB <sub>us</sub> D'E CX CE			UL <sub>us</sub> CB <sub>us</sub> D'E CX CE					
Altezza x lunghezza x spessore Height x length x thickness	50.3 x 57.0 x 8 mm			50.3 x 57.0 x 8 mm			55.7 x 55.5 x 6 mm			68.0 x 84.0 x 6 mm					
Conduttori connettibili Connection Possibility	Flessibili Flexible			0.25 ÷ 4.0 mm <sup>2</sup>			0.25 ÷ 4.0 mm <sup>2</sup>			0.25 ÷ 4.0 mm <sup>2</sup>			0.25 ÷ 2.5 mm <sup>2</sup>		
	Rigidi Solid			0.25 ÷ 6.0 mm <sup>2</sup>			0.25 ÷ 6.0 mm <sup>2</sup>			0.25 ÷ 6.0 mm <sup>2</sup>			0.25 ÷ 4.0 mm <sup>2</sup>		
Lunghezza spelatura cavo Cable stripping length	9.5 mm			9.5 mm			9 mm			9 mm					
	IEC 60947-7-1	UL 1059	CSA 22.2-158	IEC 60947-7-1	UL 1059	CSA 22.2-158	IEC 60947-7-1	UL 1059	CSA 22.2-158	IEC 60947-7-1	UL 1059	CSA 22.2-158			
Tensione nominale Voltage Rating	1000 V	600 V	600 V	1000 V	600 V	600 V	500 V	600 V	300 V	500 V	300 V	300 V			
Corrente nominale Current Rating	6.3 A	10 A	10 A	6.3 A	10 A	6.3 A	32 A	35 A	35 A	24 A	25 A	25 A			
Coppia di serraggio Tightening torque range	0.5 Nm	7 lb-in	7 lb-in	0.5 Nm	7 lb-in	7 lb-in	0.5 Nm	7 lb-in	7 lb-in	0.4 Nm	4.5 lb-in	4.5 lb-in			

Blocchetto terminale End clamp		<b>CA702</b>		<b>CA702</b>	
		<b>CA802</b>		<b>CA802</b>	
Ponte di paral- lelo preassemblato  Preassembled shorting links		2 poli - poles	<b>CA711.2</b> I <sub>max</sub> : 32A	2 poli - poles	<b>CA711.2</b> I <sub>max</sub> : 32A
		3 poli - poles	<b>CA711.3</b> I <sub>max</sub> : 32A	3 poli - poles	<b>CA711.3</b> I <sub>max</sub> : 32A
		4 poli - poles	<b>CA711.4</b> I <sub>max</sub> : 32A	4 poli - poles	<b>CA711.4</b> I <sub>max</sub> : 32A
		10 poli - poles	<b>CA711.10</b> I <sub>max</sub> : 32A	10 poli - poles	<b>CA711.10</b> I <sub>max</sub> : 32A

# Morsetti di terra da quadro

## Ground earth terminal blocks



Articolo Giallo/Verde Item Yellow/Green		CGT4			CGT6			CGT10			CGT16			CGT35		
Certificazioni Approval																
Altezza x lunghezza x spessore  Height x length x thickness		47.0 x 54.2 x 6 mm			48.2 x 54.5 x 8 mm			51.0 x 45.0 x 10 mm			48.5 x 55.0 x 12 mm			63.2 x 58.0 x 16 mm		
Conduttori connettibili  Connection Possibility	Flessibili Flexible	0.25 ÷ 4.0 mm <sup>2</sup>			0.25 ÷ 6.0 mm <sup>2</sup>			0.25 ÷ 10.0 mm <sup>2</sup>			0.25 ÷ 16.0 mm <sup>2</sup>			2.5 ÷ 35.0 mm <sup>2</sup>		
	Rigidi Solid	0.25 ÷ 6.0 mm <sup>2</sup>			0.25 ÷ 10.0 mm <sup>2</sup>			0.25 ÷ 16.0 mm <sup>2</sup>			0.25 ÷ 16.0 mm <sup>2</sup>			2.5 ÷ 35.0 mm <sup>2</sup>		
Lunghezza spelatura cavo  Cable stripping length		9 mm			12 mm			12 mm			16 mm			18 mm		
		IEC 60947-7-1	UL 1059	CSA 22.2-158	IEC 60947-7-1	UL 1059	CSA 22.2-158	IEC 60947-7-1	UL 1059	CSA 22.2-158	IEC 60947-7-1	UL 1059	CSA 22.2-158	IEC 60947-7-1	UL 1059	CSA 22.2-158
Tensione nominale Voltage Rating		800 V			800 V			800 V			800 V			800 V		
Corrente nominale Current Rating		32 A			41 A			57 A			76 A			125 A		
Coppia di serraggio Tightening torque range		0.4 Nm	7 lb-in	7 lb-in	0.5 Nm	7 lb-in	7 lb-in	1.2 Nm	14 lb-in	14 lb-in	2.0 Nm	14 lb-in	14 lb-in	2.5 Nm	25 lb-in	25 lb-in