

## Raccordi per tubo rigido Fittings for rigid pipe

<b>Materiale Raccordi:</b> Poliammide senza alogeni <b>Colore:</b> Grigio RAL7035 <b>Resistenza al fuoco:</b> UL94V0 <b>Temperatura d'esercizio:</b> -25°C +90°C <b>Conformità:</b> CE, RoHS 2015/863/EU				<b>Fittings material:</b> Polyamide halogen free <b>Colour:</b> Grey RAL7035 <b>Fire resistant:</b> UL94V0 <b>Working temperature:</b> -25°C +90°C <b>Compliance:</b> CE, RoHS 2015/863/EU		
Per tubo For pipe	Accessori IP67 Accessories IP67				Accessori IP40 Accessories IP40	
	Tubo/Scatola Pipe/Box	Tubo/Tubo Pipe/Pipe	Curva Tubo/Tubo Bend Pipe/Pipe	Curva flex Tubo/Tubo Flex bend Pipe/Pipe	Tubo/Tubo Pipe/Pipe	Curva Tubo/Tubo Bend Pipe/Pipe
Ø16 mm	<b>RTS16</b>	<b>RTT16</b>	<b>RCS16</b>	<b>RCF16</b>	<b>MC16</b>	<b>CSR16</b>
Ø20 mm	<b>RTS20</b>	<b>RTT20</b>	<b>RCS20</b>	<b>RCF20</b>	<b>MC20</b>	<b>CSR20</b>
Ø25 mm	<b>RTS25</b>	<b>RTT25</b>	<b>RCS25</b>	<b>RCF25</b>	<b>MC25</b>	<b>CSR25</b>
Ø32 mm	<b>RTS32</b>	<b>RTT32</b>	<b>RCS32</b>	<b>RCF32</b>	<b>MC32</b>	<b>CSR32</b>
Ø40 mm	<b>RTS40</b>	<b>RTT40</b>	<b>RCS40</b>	<b>RCF40</b>	<b>MC40</b>	<b>CSR40</b>
Ø50 mm	<b>RTS50</b>	<b>RTT50</b>	-	<b>RCF50</b>	<b>MC50</b>	<b>CSR50</b>

## Giunti per tubo corrugato flessibile Joints for flexible corrugated pipe



<b>Materiale Raccordi:</b> Polipropilene <b>Colore:</b> Grigio RAL7035 <b>Resistenza al fuoco:</b> UL94V0 <b>Temperatura d'esercizio:</b> -5°C +95°C <b>Conformità:</b> CE, RoHS 2015/863/EU <b>Fittings material:</b> Polypropylene <b>Colour:</b> Grey RAL7035 <b>Fire resistant:</b> UL94V0 <b>Working temperature:</b> -5°C +95°C <b>Compliance:</b> CE, RoHS 2015/863/EU	
--	--



I giunti **GCS** sono adatti alle gettate liquide per pavimentazioni in calcestruzzo cellulare  
 Joints **GCS** are suitable for cast concrete for cellular concrete floors

Per tubo For pipe		
	Tubo/Tubo Pipe/Pipe	
Ø16 mm	<b>GC16</b>	<b>GCS16</b>
Ø20 mm	<b>GC20</b>	<b>GCS20</b>
Ø25 mm	<b>GC25</b>	<b>GCS25</b>
Ø32 mm	<b>GC32</b>	<b>GCS32</b>

