



Fascette per cablaggio Cable ties



Materiale: Poliammide 6.6 (Senza Alogeni)
Temperatura d'esercizio: -40°C +85°C
Temperatura di installazione: -10°C +60°C
Resistenza alla fiamma: UL94 V2
Conformità: CE, RoHS 2015/863/UE
Material: Polyamide 6.6 (Halogen Free)
Working temperature: -40°C +85°C
Installation temperature: -10°C +60°C
Flammability resistance: UL94 V2
Compliance: CE, RoHS 2015/863/UE

Dimensioni Dimensions				
	mm	Neutro Neutral	Nero Black	
100 x 2,5	F10025	F10025N		
140 x 2,5	F14025	F14025N		
160 x 2,5	F16025	F16025N		
200 x 2,5	F20025	F20025N		
140 x 3,6	F14036	F14036N		
200 x 3,6	F20036	F20036N		
280 x 3,6	F29036	F29036N		
370 x 3,6	F36036	F36036N		
160 x 4,8	F16048	F16048N		
200 x 4,8	F20048	F20048N		
250 x 4,8	F25048	F25048N		
280 x 4,8	F29048	F29048N		
350 x 4,8	F36048	F36048N		
380 x 4,8	F39048	F39048N		
430 x 4,8	F43048	F43048N		
200 x 7,6	F20076	F20076N		
250 x 7,6	F25076	F25076N		
300 x 7,6	F30076	F30076N		
350 x 7,6	F36076	F36076N		
550 x 7,6	F54076	F54076N		
760 x 9,0	F78090	F78090N		

Fascette per cablaggio Cable ties



Materiale: Poliammide 6.6 (Senza Alogeni)
Temperatura d'esercizio: -40°C +85°C
Temperatura di installazione: -10°C +60°C
Resistenza alla fiamma: UL94 V2
Conformità: CE, RoHS 2015/863/UE
Material: Polyamide 6.6 (Halogen Free)
Working temperature: -40°C +85°C
Installation temperature: -10°C +60°C
Flammability resistance: UL94 V2
Compliance: CE, RoHS 2015/863/UE

Dimensioni Dimensions				
	mm	Neutro Neutral	Nero Black	
100 x 2,5	F10025I	F10025IN		
135 x 2,5	F14025I	F14025IN		
160 x 2,6	F16025I	F16025IN		
200 x 2,6	F20025I	F20025IN		
140 x 3,5	F14036I	F14036IN		
200 x 3,5	F20036I	F20036IN		
290 x 3,5	F29036I	F29036IN		
370 x 3,5	F36036I	F36036IN		
160 x 4,5	F16048I	F16048IN		
200 x 4,5	F20048I	F20048IN		
250 x 4,8	F25048I	F25048IN		
290 x 4,5	F29048I	F29048IN		
360 x 4,5	F36048I	F36048IN		
390 x 4,5	F39048I	F39048IN		
430 x 4,5	F43048I	F43048IN		
180 x 7,8	F20076I	F20076IN		
240 x 7,5	F25076I	F25076IN		
300 x 7,5	F30076I	F30076IN		
365 x 7,5	F36076I	F36076IN		
450 x 7,5	F45076I	F45076IN		
750 x 7,5	F75076I	F75076IN		
500 x 12,5	F500125I	F500125IN		
1000 x 12,5	F1000125I	F1000125IN		

Fascette da installazione con testa doppia Installation cable ties with double head

Materiale: Poliammide 6.6 (Senza Alogeni) Temperatura d'esercizio: -40°C +85°C Temperatura di installazione: -10°C +85°C Resistenza alla fiamma: UL94 V2 Conformità: CE, RoHS 2015/863/UE			Material: Polyamide 6.6 (Halogen Free) Working temperature: -40°C +85°C Installation temperature: -10°C +85°C Flammability resistance: UL94 V2 Compliance: CE, RoHS 2015/863/UE		
Dimensioni Dimensions	Articolo Item	Tenuta Load			
FI18090N	180 x 9 mm	40 Kg			
FI26090N	260 x 9 mm	50 Kg			
FI36090N	350 x 9 mm	50 Kg			

Fascette per siglatura Cable ties for marking

Materiale: Poliammide 6.6 (Senza Alogeni) Colore: Neutro Temperatura d'esercizio: -40°C +85°C Temperatura di installazione: -10°C +60°C Resistenza alla fiamma: UL94 V2 Conformità: CE, RoHS 2015/863/UE Material: Polyamide 6.6 (Halogen Free) Colour: Neutral Working temperature: -40°C +85°C Installation temperature: -10°C +60°C Flammability resistance: UL94 V2 Compliance: CE, RoHS 2015/863/UE		
		
Articolo Item	Dimensioni Dimensions	
	Fascetta Cable tie	Targhetta Plate
FTS10025	110 x 2,5	20 x 10 mm
FTS20025	200 x 3,6	25 x 15 mm

Fascette per siglatura Cable ties for marking

Materiale: Poliammide 6.6 (Senza Alogeni) Colore: Neutro Temperatura d'esercizio: -40°C +85°C Temperatura di installazione: -10°C +60°C Resistenza alla fiamma: UL94 V2 Conformità: CE, RoHS 2015/863/UE Material: Polyamide 6.6 (Halogen Free) Colour: Neutral Working temperature: -40°C +85°C Installation temperature: -10°C +60°C Flammability resistance: UL94 V2 Compliance: CE, RoHS 2015/863/UE		
		
Articolo Item	Dimensioni Dimensions	
	Fascetta Cable tie	Targhetta Plate
FT10025	100 x 2,5	25 x 8 mm
FT20025	200 x 2,5	25 x 8 mm