

Canali copricavo in gomma naturale Drive-over cable ramp of natural rubber

| Materiale: TPR/TPU Colore: Nero o giallo Temperatura di esercizio: -20°C +70°C Campo di durezza: 78 ± 5 | | | Material: TPR/TPU Colour: Black or yellow Working temperature: -20°C +70°C Hardness field: 78 ± 5 | | |
|--|----------------|------------------|--|---------|---------|
| | | | | | |
| Articolo Item | Peso Weight | Colore Colour | A mm | B mm | C mm |
| ZPU1B | 1,35 kg | Nero Black | 1.000 | 130 | 20 |
| ZPU1Y | | Giallo Yellow | | | |
| | | | <p>1 Scomparto - Channel 40x15 mm</p> | | |

Canali copricavo in poliuretano TPU Drive-over cable ramp of polyurethane TPU

| Materiale: TPU (Poliuretano termoplastico) Colore: Nero Temperatura di esercizio: -25°C +60°C Campo di durezza: 92A | | | Material: TPU (Thermoplastic polyurethane) Colour: Black Working temperature: -25°C +60°C Hardness field: 92A | | |
|--|----------------|---|--|---------|---------|
| | | | | | |
| Articolo Item | Peso Weight | Capacità di carico Load capacity | A mm | B mm | C mm |
| ZCU1 | 1,3 Kg | 200 Kg | 900 | 140 | 20 |
| ZCU2 | 3,8 kg | 5 tons | 900 | 275 | 40 |
| | | | <p>1 Scomparto - Channel 28x18 mm</p> | | |
| | | | <p>1 Scomparto - Channel 28x18 mm</p> | | |